

Single phase reversible autotransformers "NEW SB" RANGE

for household appliances, insulation class E, input 230V output 110V

The SB REVERSIBLE AUTOTRANSFORMERS are one of the most popular items distributed by k-factor since 1980 in the Middle-East countries. The first introducing the new double use sockets (European and US), and the polycarbonate covers. Polycarbonate covers provide a better isolation from the transformers' heating and they are totalt rust-free.

Ask for the various versions available: **110/220V, 127/220V, 110/240V, 127/240V**

On request, a model with **UK standard sockets** is available

TECHNICAL SPECIFICATION

Rated power:	100:10.000VA
Input voltage:	110/220V
Output voltage:	220/110V
Frequency:	50/60 Hz
Standards applied:	CEI 96-13 EN61558-2-13

ACCESSORIES INCLUDED

Enlarged voltage labels	YES
Single carton packing	UP TO 3KVA
Supply cord	NOT SUPPLIED
Connections through terminal blocks:	3kVA and above



From 100 to 5KVA



From 7.5 to 10kVA



MBT02 IP32 ENCLOSURE

Other accessories and fittings as per our general catalogue

Mod.	Power	W (mm.)	D (mm.)	H (mm.)	multiple carton	Weight (kg)
SBIT0100121	100VA	78	92	105	10 units	0.95
SBIT0200121	200VA	78	92	115	10 units	1.50
SBIT0300121	300VA	78	92	125	10 units	1.90
SBIT0500121	500VA	88	105	130	9 units	2.70
SBIT1000121	1000VA	105	125	135	6 units	3.80
SBIT1500121	1500VA	105	125	150	6 units	5.10
SBIT2000121	2000VA	105	125	155	6 units	5.70
SBIT3000121	3000VA	130	157	210	4 units	8.00
SBIT4000121	4000VA	130	157	220	4 units	9.30
SBIT5000121	5000VA	130	157	230	4 units	10.80
SBIT7500121	7500VA	195	190	140	1 unit	19.00
SBIT10000121	10000VA	195	190	170	1 unit	25.00

Enclosure: SUITABLE FOR SB7500-SB10000 ONLY

MBT02	7.5-10KVA	350	280	280	1 unit	3.00
-------	-----------	-----	-----	-----	--------	------

Dimensions and weight may be subject to a change without notice